



Glass Reinforced Nylon Quick-Acting Couplings

Agriculture • Construction


Glass Reinforced Nylon Part A Male Adapter x Female NPT

	Part Number	Size	Weight Each	Standard Carton	List Price Each
	GRA100	1"	0.16	70	
	GRA150	1 1/2"	0.18	30	
	GRA200	2"	0.26	40	
	GRA300	3"	0.46	35	
	GRA400	4"	0.92	20	


Glass Reinforced Nylon Part D Female Coupler x Female NPT

	Part Number	Size	Weight Each	Standard Carton	List Price Each
	GRD100●	1"	0.18	30	
	GRD150●	1 1/2"	0.50	30	
	GRD200●	2"	0.58	40	
	GRD300●	3"	1.04	20	
	GRD400●■	4"	1.48	10	
	<i>(3 Locking Handles)</i>				


Glass Reinforced Nylon Part B Female Coupler x Male NPT

	Part Number	Size	Weight Each	Standard Carton	List Price Each
	GRB100●	1"	0.16	30	
	GRB150●	1 1/2"	0.46	30	
	GRB200●	2"	0.52	50	
	GRB300●	3"	1.02	25	
	GRB400●■	4"	1.34	25	
	<i>(3 Locking Handles)</i>				


Glass Reinforced Nylon Part E Male Adapter x Hose Shank

	Part Number	Size	Weight Each	Standard Carton	List Price Each
	GRE100	1"	0.02	50	
	GRE150	1 1/2"	0.18	40	
	GRE200	2"	0.28	50	
	GRE300	3"	0.66	18	
	GRE400	4"	1.04	20	

Glass Reinforced Nylon Part C Female Coupler x Hose Shank

	Part Number	Size	Weight Each	Standard Carton	List Price Each
	GRC100●	1"	0.18	60	
	GRC150●	1 1/2"	0.50	30	
	GRC200●	2"	0.58	40	
	GRC300●	3"	1.24	15	
	GRC400●■	4"	1.60	15	
	<i>(3 Locking Handles)</i>				

Glass Reinforced Nylon Part F Male Adapter x Male NPT

	Part Number	Size	Weight Each	Standard Carton	List Price Each
	GRF100	1"	0.10	45	
	GRF150	1 1/2"	0.18	50	
	GRF200	2"	0.28	60	
	GRF300	3"	0.66	20	
	GRF400	4"	0.90	25	

● These couplers are supplied with locking feature . . . safety clips may be inserted to lock handles, preventing disconnection during product transfer.

■ All 4" couplers are supplied with 3 locking handles to provide additional stability and prevent wobbling.

All coupler parts are supplied with LTW (Lifetime Warranted) Investment Cast Stainless Steel Handles.

NOTE: See Chemical Resistance Chart on Pages 29 – 31

Material Specifications & Operating Pressure

	Body	Handles	Slot Pins	Pull Rings	Gaskets	Safety Clips	Operating Pressure
Glass Reinforced Nylon	Fiberglass-reinforced Nylon, for high tensile strength, light weight and rigidity.	Type 316 LTW stainless steel	Type 316 stainless steel	Stainless steel	EPDM	Stainless steel	1": 175 PSI 1 1/2" – 2": 150 PSI 3": 125 PSI 4": 75 PSI Temperature Range: -30° F – +200° F

NOTE: All parts on this page are fully interchangeable with any other adapters made to MIL Specs.

All prices and specifications subject to change without notice.