


Polypropylene Quick-Acting Couplings

Agriculture • Construction



90° Male Adapter
x Female NPT



90° Female Coupler
x Female NPT

Polypropylene 90° Male Adapter x Female NPT

| Part Number | Size | Weight Each | Standard Carton | List Price Each |
|-------------|--------|-------------|-----------------|-----------------|
| PP150A90 | 1 1/2" | 0.23 | 24 | \$ 4.54 |
| PP200A90 | 2" | 0.36 | 24 | 5.18 |

Polypropylene 90° Female Coupler x Female NPT

| Part Number | Size | Weight Each | Standard Carton | List Price Each |
|-------------|--------|-------------|-----------------|-----------------|
| PP150D90● | 1 1/2" | 0.65 | 24 | \$ 9.34 |
| PP200D90● | 2" | 0.78 | 24 | 11.58 |



90° Female Coupler
x Hose Shank



90° Male Adapter
x Male NPT

Polypropylene 90° Female Coupler x Hose Shank

| Part Number | Size | Weight Each | Standard Carton | List Price Each |
|-------------|--------|-------------|-----------------|-----------------|
| PP150C90● | 1 1/2" | 0.56 | 24 | \$ 9.34 |
| PP200C90● | 2" | 0.73 | 24 | 11.58 |

Polypropylene 90° Male Adapter x Male NPT

| Part Number | Size | Weight Each | Standard Carton | List Price Each |
|-------------|--------|-------------|-----------------|-----------------|
| PP150F90 | 1 1/2" | 0.27 | 24 | \$ 5.44 |
| PP200F90 | 2" | 0.41 | 24 | 5.82 |

- These couplers are supplied with locking feature . . . safety clips may be inserted to lock handles, preventing disconnection during product transfer.



PPN Series

Combination Hose Nipples — PPN Series (Polypropylene)

NPT Thread

| Part Number | Size | Weight Each | Standard Carton | List Price Each |
|-------------|--------|-------------|-----------------|-----------------|
| PPN050 | 1/2" | 0.03 | 400 | \$ 0.65 |
| PPN075 | 3/4" | 0.06 | 200 | 0.74 |
| PPN100 | 1" | 0.07 | 100 | 0.88 |
| PPN125 | 1 1/4" | 0.11 | 80 | 0.99 |
| PPN150 | 1 1/2" | 0.13 | 60 | 1.22 |
| PPN200 | 2" | 0.22 | 40 | 1.48 |
| PPN300 | 3" | 0.55 | 12 | 5.10 |

NOTE: See Chemical Resistance Chart on Pages 29 – 31

Temperature Range: 0° F. to 150° F.

Material Specifications & Operating Pressure

| | Body | Handles | Slot Pins | Pull Rings | Gaskets | Safety Clips | Operating Pressure |
|---------------|--|--|--------------------------|-----------------|---------|-----------------|---|
| Polypropylene | Polypropylene is glass-filled for added strength and durability. | Type 316 Investment Cast stainless steel | Type 304 stainless steel | Stainless steel | EPDM | Stainless steel | 1/2" – 2": 100 PSI @ 0°F, 125 PSI @ 70°F, 70 PSI @ 150°F; 3" – 4": 75 PSI @ 70°F. |

NOTE: All parts on this page are fully interchangeable with any other adapters made to MIL Specs.

All prices and specifications subject to change without notice.