

Exstatic®

APPLICATION:

Goodyear's Exstatic® hose is for tank truck and/or in-plant transfer of dry, bulk foodstuffs where there is a potential for electrical static build-up.

CONSTRUCTION:

TUBE: FDA UHMWPE (static dissipating/static conductive) has FDA/USDA compliant materials

COVER: Blue Plioflex® synthetic rubber (corrugated)/spiral transfer brand(wrapped impression)

REINFORCEMENT: Spiral-plyed synthetic fabric with double wire helix



TEMPERATURE: -25°F to 180°F (-32°C to 82°C)

PACKAGING: 100' length, coiled, polywrapped

BRANDING: Continuous spiral brand "Goodyear™ Plicord Exstatic FDA Dry Material handling 150 psi."

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure. Use Goodyear's Insta-Lock Cam Groove Fittings with this product. See page 221 for available Insta-Lock products.

NON-STOCK/SIZES: Refer to page 300 for special production run minimum requirements.

ORDER CODES: 549-608

| ID | | NOM. OD | | MAX. WP | | Bend Radius | | Vacuum HG | | WEIGHT | |
|-----|-------|---------|-------|---------|------|-------------|-----|-----------|-----|---------|--------|
| in. | mm. | in. | mm. | psi. | Mpa. | in. | mm. | in. | mm. | lb./ft. | kg./m. |
| 2 | 50.8 | 2.50 | 63.5 | 150 | 1.03 | 8 | 203 | 29 | 737 | 1.07 | 1.59 |
| 3 | 76.2 | 3.56 | 90.4 | 150 | 1.03 | 12 | 305 | 29 | 737 | 1.83 | 2.72 |
| 4 | 101.6 | 4.59 | 116.6 | 150 | 1.03 | 16 | 406 | 29 | 737 | 2.49 | 3.71 |
| 5 | 127.0 | 5.67 | 144.0 | 150 | 1.03 | 20 | 508 | 29 | 737 | 3.69 | 5.49 |