

# Harvest™

## APPLICATION:

For tank truck and/or in-plant applications for the transfer of dry, nonoily bulk foodstuffs.

## CONSTRUCTION:

TUBE: FDA, White Pureten™ synthetic rubber

COVER: Gray Versigard® synthetic rubber (corrugated)/orange branding tape (wrapped impression)

REINFORCEMENT: Spiral-plyed synthetic fabric with double galvanized wire helix



TEMPERATURE: -25°F to 180°F (-32°C to 82°C)

PACKAGING: 100' length, coiled, polywrapped

BRANDING: Continuous spiral brand "Goodyear™ Harvest 150 psi WP; FDA/USDA."

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

NON-STOCK/SIZES: Refer to page 300 for special production run minimum requirements.

ORDER CODES: 549-627

ID		NOM. OD		MAX. WP		Bend Radius		Vacuum HG		WEIGHT	
in.	mm.	in.	mm.	psi.	Mpa.	in.	mm.	in.	mm.	lb./ft.	kg./m.
2	50.8	2.73	69.3	150	1.03	5	127	29	737	1.57	2.34
3	76.2	3.74	95.0	150	1.03	7	178	29	737	2.32	3.46
4	101.6	4.78	121.4	150	1.03	10	257	29	737	3.44	5.12
5	127.0	5.91	150.1	150	1.03	15	381	29	737	4.76	7.08