

# Plicord® Blue Flour

**APPLICATION:**

Tank truck or in-plant service hose is for discharge transfer of abrasive materials and dry foods such as flour, cake mixes, etc.



**CONSTRUCTION:**

**TUBE:** 3/16" gauge white Pureten™ tube (FDA compliant)

**COVER:** Blue Plioflex™ rubber (wrapped impression)

**REINFORCEMENT:** Spiral-plyed synthetic fabric with 2 antistatic wires

**TEMPERATURE:** -40°F to 180°F (-40°C to 82°C)

**PACKAGING:** 100' length, coiled, polywrapped

**BRANDING:** Continuous spiral brand example "Goodyear™ Plicord Blue Flour Discharge FDA 150 psi."

**COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

**NON-STOCK/SIZES:** Refer to page 300 for special production run minimum requirements.

**ORDER CODES:** 549-503

ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm.	in.	mm.	psi.	Mpa.	lb./ft.	kg./m.
2	50.8	2.68	68.1	150	1.03	1.39	2.07
3	76.2	3.69	93.7	150	1.03	2.02	3.01
4	101.6	4.71	119.6	150	1.03	2.63	3.91
5	127.0	5.72	145.3	150	1.03	3.27	4.87