

Plicord® Gray Food

APPLICATION:

A flexible hose for gravity flow, pressure, or suction service transferring edibles from tank truck and in-plant service.

CONSTRUCTION:

TUBE: White Chemivoc® synthetic rubber (FDA/USDA compliant and conforms to 3-A Sanitary Standard 18-03)

COVER: Gray Chemivoc® synthetic rubber (wrapped impression)

REINFORCEMENT: Spiral-plyed synthetic fabric with Galvanized Wire helix



TEMPERATURE: -25°F to 212°F (-32°C to 100°C)

PACKAGING: 100' length, coiled, polywrapped

BRANDING: Continuous spiral brand "Goodyear™ Plicord Gray Food; FDA, 3-A, and USDA 150 psi."

COUPLINGS: Use Goodyear's Insta-Lock Cam & Groove Fittings with this product. See page 221 for available Insta-Lock products.

NON-STOCK/SIZES: Refer to page 300 for special production run minimum requirements.

ORDER CODES: 549-834

ID	NOM. OD		MAX. WP		Bend Radius		Vacuum HG		WEIGHT			
	in.	mm.	in.	mm.	psi.	Mpa.	in.	mm.	lb./ft.	kg./m.		
1	25.4	1.45	36.7		150	1.03	3	75	29	737	0.58	0.86
1 1/2	38.1	1.97	50.0		150	1.03	4	102	29	737	0.85	1.26
2	50.8	2.59	65.8		150	1.03	5	114	29	737	1.42	2.11
2 1/2	63.5	3.09	78.5		150	1.03	6	152	29	737	1.77	2.63
3	76.2	3.59	91.2		150	1.03	7	178	29	737	2.10	3.13
4	101.6	4.68	118.9		150	1.03	10	254	29	737	3.19	4.75