

Plicord® Winline®

APPLICATION:

A quality, nontoxic hose for handling wine, potable water, and other nonoily liquid food products where the hose must meet FDA requirements. For discharge service and suction service up to 20" hg vacuum at ambient temperature.



CONSTRUCTION:

TUBE: White chlorobutyl rubber (FDA/USDA compliant and conforms to 3-A Sanitary Standard 18-03)

COVER: White Versigard® rubber with a purple spiral stripe (wrapped impression)

REINFORCEMENT: Spiral-plyed synthetic fabric, 4 plies to 1 1/2" I.D.; 6 plies over 1 1/2" I.D.

TEMPERATURE: -40°F to 220°F (-40°C to 104°C)

PACKAGING: 100' length, coiled, polywrapped

BRANDING: Continuous spiral brand "Goodyear™ Plicord Winline hose 250 psi; FDA, 3-A, and USDA."

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

NON-STOCK/SIZES: Refer to page 300 for special production run minimum requirements.

ORDER CODES: 549-887

ID		NOM. OD		MAX. WP		Vacuum		WEIGHT	
in.	mm.	in.	mm.	psi.	Mpa.	in.	mm.	lb./ft.	kg./m.
3/4	19.1	1.34	35.3	250	1.72	20	508	0.60	0.89
1	25.4	1.69	42.9	250	1.72	20	508	0.80	1.19
1 1/4	31.8	2.00	50.8	250	1.72	20	508	1.04	1.55
1 1/2	38.1	2.23	56.6	250	1.72	20	508	1.20	1.79
2	50.8	2.92	74.2	250	1.72	20	508	1.98	2.95
2 1/2	63.5	3.50	88.2	250	1.72	20	508	2.65	3.94
3	76.2	4.09	103.9	250	1.72	20	508	3.55	5.28
4	101.6	5.30	134.6	250	1.72	20	508	5.40	8.04