

Sani-Wash™ 300

APPLICATION:

An economical hose for hot water washdown up to 205°F cleanup in food processing plants, dairies, packing houses, bottling plants, breweries, canneries, and creameries.



CONSTRUCTION:

TUBE: Versigard® synthetic rubber

COVER: White Versigard synthetic rubber

REINFORCEMENT: Textile reinforced

TEMPERATURE: -40°F to 200°F (-40°C to 93°C)

PACKAGING: 1/2"-3/4" 500' reels, maximum 3 pieces, 50' increments / 1" 450' reels, maximum 3 pieces, 50' increments

BRANDING: Brand example "Goodyear™ Sani-Wash 300 psi WP 3/4" (19.1 mm) Made in USA."

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

NON-STOCK/SIZES: Refer to page 300 for special production run minimum requirements.

ORDER CODES: 569-020

ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm.	in.	mm.	psi	Mpa	lb./ft.	kg./m.
1/2	12.7	0.84	21.3	300	2.07	0.26	0.39
5/8	15.9	1.00	25.4	300	2.07	0.31	0.46
3/4	19.1	1.17	29.7	300	2.07	0.42	0.63
1	25.4	1.47	37.3	300	2.07	0.62	0.92