

Spectra™ 1000

[Products](#) > [Food](#)

APPLICATION:

For use on pressure washer machines with working pressures up to 1000 psi. Its oil-resistant cover provides protection against the effects of oil and animal fats.

CONSTRUCTION:

TUBE: Nitrile synthetic rubber

COVER: Yellow oil-resistant synthetic rubber, RMA Class A (High Oil Resistance)

REINFORCEMENT: Braided (1) steel wire

TEMPERATURE: -20°F to 250°F (-29°C to 121°C)

PACKAGING: 500' reel, maximum 3 pieces, 50' increments, coupled lengths available

BRANDING: Continuous brand example "Spectra™ 1000 3/8" 1000 psi WP. Made in USA by Goodyear™."

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

NON-STOCK/SIZES: Refer to page 300 for special production run minimum requirements.

ORDER CODES: 539-404



| ID | | NOM. OD | | MAX. WP | | WEIGHT | |
|-----|------|---------|------|---------|------|---------|--------|
| in. | mm. | in. | mm. | psi | Mpa | lb./ft. | kg./m. |
| 3/8 | 9.5 | 0.69 | 17.5 | 1000 | 6.90 | 0.23 | 0.34 |
| 1/2 | 12.7 | 0.81 | 20.6 | 1000 | 6.90 | 0.29 | 0.42 |
| 3/4 | 19.1 | 1.10 | 27.9 | 1000 | 6.90 | 0.42 | 0.63 |

Note: Not recommended for steam service.