

Spectra™ 300

APPLICATION:

A high quality, economical construction for hot water up to 200°F (93°C) cleanup service in food processing plants, dairies, packing houses, bottling plants, breweries, canneries, and creameries.



CONSTRUCTION:

TUBE: Black Nitrile synthetic rubber, RMA Class A (High Oil Resistance), non-FDA

COVER: White Chemivic® synthetic rubber, RMA Class A (High Oil Resistance)

REINFORCEMENT: Spiral synthetic yarn

TEMPERATURE: -20°F to 200°F (-29°C to 93°C)

PACKAGING: 1/2"-3/4" 500' reels, maximum 3 pieces, 50' increments / 1" 450' reels, maximum 3 pieces, 50' increments

BRANDING: Continuous brand example "Spectra (19.1 mm) 300 psi WP. Made in USA by Goodyear™."

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

NON-STOCK/SIZES: Refer to page 300 for special production run minimum requirements.

ORDER CODES: 569-019

ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm.	in.	mm.	psi	Mpa	lb./ft.	kg./m.
1/2	12.7	0.91	23.1	300	2.07	0.27	0.40
3/4	19.1	1.18	30.0	300	2.07	0.40	0.60
1	25.4	1.50	38.1	300	2.07	0.60	0.89