

Spectra™ 3000

APPLICATION:

For use on pressure washer machines with working pressures up to 3000 psi. Its oil-resistant cover provides protection against the effects of oil and animal fats.



CONSTRUCTION:

TUBE: Nitrile synthetic rubber

COVER: Yellow oil-resistant synthetic rubber, RMA Class A (High Oil Resistance)

REINFORCEMENT: Braided (1) steel wire

TEMPERATURE: -20°F to 250°F (-29°C to 121°C)

PACKAGING: 500' reels, maximum 3 pieces, 50' increments, coupled lengths available

BRANDING: Continuous brand example "Spectra™ 3000 3/8" 3000 psi W.P. Made in USA by Goodyear™."

COUPLINGS: Use Goodyear's pressure washer fittings with this product. See page 235 for available sizes. Refer to Goodyear's Hose Assembly Manual for crimp procedures. Coupled lengths with MxMS fittings and Kink Guards available.

NON-STOCK/SIZES: Refer to page 300 for special production run minimum requirements.

ORDER CODES: 539-413

ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm.	in.	mm.	psi	Mpa	lb./ft.	kg./m.
1/4	6.4	0.54	13.7	3000	20.69	0.16	0.24
3/8	9.5	0.69	17.5	3000	20.69	0.24	0.36
1/2	12.7	0.82	20.8	3000	20.69	0.32	0.48

Note: Not recommended for steam service.