

Vintner™

APPLICATION:

For handling in-plant and/or tank truck transfer of wine, beer, potable water, and other nonoily, liquid foodstuffs.

CONSTRUCTION:

TUBE: White Chlorobutyl (FDA/USDA compliant and conforms to 3-A sanitary standard 18-03)

COVER: Gray Versigard® synthetic rubber (wrapped)/purple branding tape

REINFORCEMENT: Spiral-plyed synthetic fabric with Monofilament Helix



TEMPERATURE: -30°F to 220°F (-34°C to 104°C)

PACKAGING: 100' length, coiled, polywrapped

BRANDING: Continuous spiral brand "Goodyear™ Plicord Vintner 250 psi; FDA, 3-A, and USDA."

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

NON-STOCK/SIZES: Refer to page 300 for special production run minimum requirements.

ORDER CODES: 549-886

NOM. ID		NOM. OD		MAX. WP		BEND RADIUS		VACUUM HG		WEIGHT	
in.	mm.	in.	mm.	psi	Mpa	in.	mm.	in.	mm.	lb./ft.	kg./m.
1	25.4	1.62	41.1	250	1.72	3	76	27	686	0.71	1.06
1 1/2	38.1	2.11	53.6	250	1.72	4	102	27	686	0.98	1.46
2	50.8	2.68	68.1	250	1.72	7	178	27	686	1.38	2.05
2 1/2	63.5	3.21	81.5	250	1.72	10	254	27	686	1.78	2.65
3	76.2	3.85	97.8	250	1.72	12	305	27	686	2.59	3.86