


## White Flexwing®

### APPLICATION:

A highly flexible hose for gravity flow, pressure, or suction service transferring oily and nonoily edibles from tank truck and in-plant service.



### CONSTRUCTION:

TUBE: White Chemivic® synthetic rubber (FDA/USDA compliant and conforms to 3-A sanitary standard 18-03)

COVER: White Chemivic synthetic rubber (wrapped impression)

Reinforcement: Spiral-plied synthetic fabric with galvanized wire helix

TEMPERATURE: -25°F to 250°F (-32°C to 121°C)

PACKAGING: 100' length, coiled, polywrapped

BRANDING: Continuous spiral brand "Goodyear™ White Flexwing 150 psi WP; FDA, 3-A, and USDA."

COUPLINGS: Use Goodyear's Insta-Lock Cam & Groove Fittings with this product. See page 221 for available Insta-Lock products.

NON-STOCK/SIZES: Refer to page 300 for special production run minimum requirements.

ORDER CODES: 549-151

ID	NOM. OD		MAX. WP		Bend Radius		Vacuum HG		WEIGHT			
	in.	mm.	in.	mm.	psi.	Mpa.	in.	mm.	in.	mm.	lb./ft.	kg./m.
3/4	19.1	1.20	30.5		150	1.03	2	51	29	737	0.47	0.70
1	25.4	1.44	36.6		150	1.03	3	76	29	737	0.57	0.85
1 1/4	31.8	1.70	43.2		150	1.03	4	102	29	737	0.69	1.03
1 1/2	38.1	1.97	50.0		150	1.03	4	102	29	737	0.86	1.28
2	50.8	2.53	64.3		150	1.03	5	114	29	737	1.23	1.83
2 1/2	63.5	3.10	78.7		150	1.03	6	146	29	737	1.81	2.69
3	76.2	3.60	91.4		150	1.03	7	178	29	737	2.16	3.21
4	101.6	4.64	117.9		150	1.03	10	254	29	737	3.05	4.54
5	127.0	5.97	151.6		150	1.03	20	508	29	737	5.73	8.53