

T130AK T133AK



NEW
2 1/2" SIZE

STEEL WIRE AIR HOSE

APPLICATION

High pressure air hose for heavy-duty use in mines, quarries, construction and industry.

COVER

Yellow, SBR rubber, offering excellent abrasion and weather resistance — pin pricked.

REINFORCEMENT

High tensile spiral steel wire.

TUBE

Black SBR/NBR — resistant to oil mist.

TEMPERATURE RANGE

-22°F to 176°F

STANDARD LENGTH

50 or 100 feet

BRANDING

Embossed – ALFAGOMMA – ITALY – T130 STEEL AIR

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MAX. REC. WP (PSI)	MIN. BEND RADIUS (in.)
	(in.)	(mm)	(in.)	(mm)			
T130AK050	1/2	13	0.98	25	43	600	2 1/2
T130AK075	3/4	19	1.22	31	54	600	4
T130AK100	1	25	1.46	37	68	600	5
T130AK125	1 1/4	32	1.73	44	83	600	6
T130AK150	1 1/2	38	2.05	52	111	600	7 1/2
T130AK200	2	51	2.56	65	157	600	10
T130AK250	2 1/2	63	3.27	83	241	450	12
T130AK300	3	76	3.78	96	288	450	15
T130AK400	4	102	4.80	122	393	450	20

COUPLING SUGGESTIONS

Steel or malleable iron male insert NPT, female ground joint or washer type with spud, or universal quick-acting couplings attached with 2 or 4 bolt interlocking clamps or bands.

HIGH TEMPERATURE STEEL WIRE REINFORCED AIR HOSE

APPLICATION

High pressure air for mines and quarries. Designed for long lasting service and maximum safety in heavy duty applications where resistance to high temperature is required.

COVER

Yellow EPDM — abrasion and ozone resistant — pin pricked.

REINFORCEMENT

High tensile steel cords.

TUBE

Black Chlorobutyl.

TEMPERATURE RANGE

-31°F to +338°F

STANDARD LENGTHS

100 feet

BRANDING

ALFAGOMMA – ITALY T133 HI TEMP STEEL AIR — Embossed.

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MAX. REC. WP (PSI)	MIN. BEND RADIUS (in.)
	(in.)	(mm)	(in.)	(mm)			
◆T133AK200	2	51	2.56	65	150	600	10
●T133AK250	2 1/2	63	3.26	83	240	600	12
●T133AK300	3	76	3.70	94	276	600	15

PLEASE NOTE:

- ◆ 2" ID is braided construction.
- 2 1/2" & 3" ID have spiral construction.

COUPLING SUGGESTIONS

Steel or malleable iron male insert NPT, female ground joint or washer type with spud, or universal quick-acting couplings attached with 2 or 4 bolt interlocking clamps or bands.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE.