

T136AK T614AA



1000 PSI MINE SPRAY HOSE

APPLICATION

Underground mine water spray for dust control. Also useable on continuous mining machinery.

COVER

Yellow SBR/NBR blend — abrasion, ozone, hydrocarbon and fire resistant — pin pricked.

REINFORCEMENT

High tensile spiralled steel wire.

TUBE

Black SBR/NBR blend — oil mist resistant.

TEMPERATURE RANGE

-22°F to 200 °F

STANDARD LENGTH

50 or 100 feet

WORKING PRESSURE

Constant Pressure — 1000 PSI

BRANDING

Embossed brand ALFAGOMMA – ITALY – 70 BAR (1000 PSI) MINE SPRAY MSHA IC – 152/6

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.
	(in.)	(mm)	(in.)	(mm)	
T136AK075	3/4	19	1.14	29	46
T136AK100	1	25	1.38	35	61
T136AK125	1 1/4	32	1.65	42	79
T136AK150	1 1/2	38	1.97	50	103
T136AK200	2	51	2.56	65	153

COUPLING SUGGESTIONS

Permanently attached crimped hydraulic couplings.

HOT TAR AND ASPHALT SUCTION AND DELIVERY HOSE — 10 BAR (150 PSI)

APPLICATION

Hot tar and asphalt suction and delivery service.

COVER

Black CSM — abrasion, ozone and hot tar resistant.

REINFORCEMENT

High tensile textile cords with steel helix wires.

TUBE

Black NBR — hot tar and asphalt resistant.

TEMPERATURE RANGE

-25°F to 350°F

WORKING PRESSURE

10 Bar (150 PSI)

STANDARD LENGTH

100 feet

BRANDING

ALFAGOMMA – ITALY T614 10 BAR (150 PSI) HOT TAR AND ASPHALT (on red stripe)

SERIES NO.	NOMINAL ID		NOMINAL OD		WALL THICKNESS (mm)	APPROX. WT. lbs./100 ft.	MIN. BEND RADIUS (in.)
	(in.)	(mm)	(in.)	(mm)			
T614AA200	2	51	2.72	69	9	153	10
T614AA300	3	76	3.78	96	10	256	15
T614AA400	4	102	4.80	122	10	334	20

COUPLING SUGGESTIONS

Permanently attached couplings are suggested for assemblies.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE.