

T154AA

T155AA



HEAVY WALL/HEAVY DUTY WATER DISCHARGE HOSE

APPLICATION

Heavy duty water discharge hose where tougher operating conditions exist and high pressures are needed.

COVER

Black abrasion and weather-resistant SBR rubber.

REINFORCEMENT

High tensile textile cords.

TUBE

Black SBR/NBR blend

TEMPERATURE RANGE

-22°F to 176°F

WORKING PRESSURE

Constant Pressure — 10 Bar (150 PSI)

STANDARD LENGTH

100 feet: 1 1/2" through 8"
50 feet: 6", 8"

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MAX. REC. WP (PSI)
	(in.)	(mm)	(in.)	(mm)		
T154AA150	1 1/2	38	1.97	50	80	150
T154AA200	2	51	2.48	63	105	150
T154AA300	3	76	3.54	90	147	150
T154AA400	4	102	4.57	116	237	150
T154AA600	6	152	6.54	166	309	150
T154AA800	8	203	8.62	219	458	150

COUPLING SUGGESTIONS

Cam and groove, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of quick-couplings, pin lug shank couplings and combination nipples. Refer to your individual coupling sheets for type and pricing.

HIGH PRESSURE WATER DISCHARGE HOSE

APPLICATION

Heavy duty water discharge hose where tougher operating conditions exist and high pressures are needed.

COVER

Black abrasion and weather-resistant SBR rubber.

REINFORCEMENT

High tensile textile cords.

TUBE

Black SBR/NBR blend

TEMPERATURE RANGE

-22°F to 176°F

STANDARD LENGTH

100 feet: 1 1/2" through 6"
50 feet: 6"

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MAX. REC. WP (PSI)
	(in.)	(mm)	(in.)	(mm)		
T155AA150	1 1/2	38	1.97	50	83	300
T155AA200	2	51	2.56	65	110	300
T155AA250	2 1/2	63	3.11	79	151	300
T155AA300	3	76	3.62	92	182	300
T155AA400	4	102	4.65	118	242	300
T155AA600	6	152	6.69	170	390	225

COUPLING SUGGESTIONS

Cam and groove, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of quick-couplings, pin lug shank couplings and combination nipples. Refer to your individual coupling sheets for type and pricing.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE.