

# T155AK T157AG



## TEXTILE CORD "AIR DRILL" HOSE

### APPLICATION

High quality air hose for mining and construction service.

### COVER

Yellow, abrasion and weather-resistant SBR rubber.

### REINFORCEMENT

Spiralled, high tensile textile cords.

### TUBE

Black SBR/NBR blend — oil mist resistant.

### TEMPERATURE RANGE

-22°F to 176°F

### STANDARD LENGTH

100 feet: 1/2" through 4"

50 feet: 1/2", 1", and 2 1/2" through 4"

### BRANDING

ALFAGOMMA – ITALY – T155 20 BAR (300 PSI) AIR (in blue letters)

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MAX. REC. WP (PSI)
	(in.)	(mm)	(in.)	(mm)		
T155AK050	1/2	13	0.83	21	22	300
T155AK075	3/4	19	1.14	29	37	300
T155AK100	1	25	1.46	35	48	300
T155AK125	1 1/4	32	1.73	44	73	300
T155AK150	1 1/2	38	1.97	50	85	300
T155AK200	2	51	2.56	65	112	300
T155AK250	2 1/2	63	3.11	79	155	300
T155AK300	3	76	3.62	92	186	300
T155AK400	4	102	4.65	118	247	300

### COUPLING SUGGESTIONS

Steel or malleable iron male insert NPT, female ground joint or washer type with spud, attached with 2 or 4 bolt interlocking clamps or bands. Universal couplings may be used on sizes (1/2" – 2")

## TEXTILE CORD "HEAVY DUTY" AIR DRILL HOSE

### APPLICATION

High quality air hose for heavy duty and mining applications.

### COVER

Green, abrasion and weather-resistant SBR rubber.

### REINFORCEMENT

Spiralled, high tensile textile cords.

### TUBE

Black SBR/NBR blend — oil mist resistant.

### TEMPERATURE RANGE

-22°F to 176°F

### STANDARD LENGTH

100 feet: 1/2" through 2"

50 feet: 1/2" through 2"

### BRANDING

ALFAGOMMA – ITALY – T157 27 BAR (400 PSI) AIR (in blue letters)

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MAX. REC. WP (PSI)
	(in.)	(mm)	(in.)	(mm)		
T157AG050	1/2	13	0.83	23	28	400
T157AG075	3/4	19	1.14	29	38	400
T157AG100	1	25	1.46	35	48	400
T157AG125	1 1/4	32	1.73	44	75	400
T157AG150	1 1/2	38	1.97	50	86	400
T157AG200	2	51	2.56	65	114	400

### COUPLING SUGGESTIONS

Steel or malleable iron male insert NPT, female ground joint or washer type with spud, attached with 2 or 4 bolt interlocking clamps or bands. Universal couplings may be used on sizes (1/2" – 2")

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE.