

T155AK T902AA



TEXTILE CORD "AIR DRILL" HOSE

APPLICATION

High quality air hose for mining and construction service.

COVER

Yellow, abrasion and weather-resistant SBR rubber.

REINFORCEMENT

Spiralled, high tensile textile cords.

TUBE

Black SBR/NBR blend — oil mist resistant.

TEMPERATURE RANGE

-22°F to 176°F

STANDARD LENGTH

100 feet: 1/2" through 4"
50 feet: 1/2", 1", and 2 1/2" through 4"

BRANDING

ALFAGOMMA – ITALY – T155 20 BAR (300 PSI) AIR (in blue letters)

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MAX. REC. WP (PSI)
	(in.)	(mm)	(in.)	(mm)		
T155AK050	1/2	13	0.83	21	22	300
T155AK075	3/4	19	1.14	29	37	300
T155AK100	1	25	1.46	35	48	300
T155AK125	1 1/4	32	1.73	44	73	300
T155AK150	1 1/2	38	1.97	50	85	300
T155AK200	2	51	2.56	65	112	300
T155AK250	2 1/2	63	3.11	79	155	300
T155AK300	3	76	3.62	92	186	300
T155AK400	4	102	4.65	118	247	300

COUPLING SUGGESTIONS

Steel or malleable iron male insert NPT, female ground joint or washer type with spud, attached with 2 or 4 bolt interlocking clamps or bands. Universal couplings may be used on sizes (1/2" – 2")

HIGH QUALITY HOT AIR BLOWER HOSE

APPLICATION

Handling hot air under pressure, between the air compressor and dry bulk tank on bulk material carriers.

COVER

Black EPDM rubber — heat, abrasion and ozone resistant.

REINFORCEMENT

Spiralled high tensile textile cords and 4 highly flexible steel helix wires.

TUBE

Black heat-resistant EPDM rubber.

TEMPERATURE RANGE

-40°F to 350°F

STANDARD LENGTH

100 feet

WORKING PRESSURE

Constant Pressure — 10 Bar (150 PSI)

BRANDING

ALFAGOMMA – ITALY T902 10 BAR (150 PSI)
– HOT AIR SERVICE (in white letters)

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MIN. BEND RADIUS (in.)
	(in.)	(mm)	(in.)	(mm)		
T902AA200	2	51	2.48	63	102	6
T902AA300	3	76	3.54	90	170	9
T902AA400	4	102	4.65	116	217	12

COUPLING SUGGESTIONS

Cam and groove, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of quick-couplings, pin lug shank couplings and combination nipples. Refer to your individual coupling sheets for type and pricing.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE.