

## T202AA



### \* 150 PSI EPDM MULTI-PURPOSE WATER SUCTION HOSE

#### APPLICATION

Suction and delivery of non-corrosive liquids for irrigation, construction, fertilizers and lasso acid solutions.

#### COVER

Black weather and ozone-resistant EPDM rubber.

#### REINFORCEMENT

Spiralled high tensile textile cords and 4 highly flexible steel helix wires.

#### TUBE

Black EPDM rubber.

#### TEMPERATURE RANGE

-22°F to 176°F

#### STANDARD LENGTH

100 feet: 1" through 4"

20, 50 feet: 5"

20, 25 feet: 8"

20, 25, 50 feet: 6"

20 feet: 10", 12"

#### BRANDING

ALFAGOMMA – ITALY – T202 10 BAR (150 PSI) GENERAL PURPOSE EPDM (in green letters) EXCEPT 12" has a solid green stripe

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MAX. REC. WP (PSI)	MIN. BEND RADIUS (in.)
	(in.)	(mm)	(in.)	(mm)			
T202AA100	1	25	1.38	35	48	150	4
T202AA125	1 1/4	32	1.65	42	57	150	5
T202AA150	1 1/2	38	1.89	48	65	150	6
T202AA200	2	51	2.40	61	86	150	8
T202AA250	2 1/2	63	2.95	75	125	150	10
T202AA300	3	76	3.46	88	150	150	12
T202AA350	3 1/2	90	4.02	102	180	150	14
T202AA400	4	102	4.49	114	198	150	16
T202AA500	5	127	5.55	141	312	150	25
T202AA600	6	152	6.54	166	400	150	30
T202AA800	8	203	8.70	221	761	150	40
T202AA1000	10	254	10.71	272	905	150	50
T202AA1200	12	305	12.80	325	1500	* 90	60

\* Please note: 12" ID Maximum Working Pressure is 90 PSI

#### COUPLING SUGGESTIONS

Cam and groove, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of quick-couplings, pin lug shank couplings and combination nipples. Refer to your individual coupling sheets for type and pricing.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE.

## T204AA



### EPDM MULTI-PURPOSE WATER SUCTION HOSE

#### APPLICATION

Suction and delivery of non-corrosive liquids for irrigation, construction, fertilizers and lasso acid solutions.

#### COVER

Black weather and ozone-resistant EPDM rubber.

#### REINFORCEMENT

Spiralled high tensile textile cords and 4 highly flexible steel helix wires.

#### TUBE

Black EPDM rubber.

#### TEMPERATURE RANGE

-22°F to 176°F

#### STANDARD LENGTH

20, 25, 30, 50, 100 feet: 6"

20, 25, 50 feet: 8"

20 feet: 10"

#### BRANDING

ALFAGOMMA – ITALY – T204 (embossed)

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MAX. REC. WP (PSI)	MIN. BEND RADIUS (in.)
	(in.)	(mm)	(in.)	(mm)			
T204AA600	6	152	6.54	166	380	75	30
T204AA800	8	203	8.70	221	650	75	40
T204AA1000	10	254	10.71	272	875	45	50

#### COUPLING SUGGESTIONS

Cam and groove, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of quick-couplings, pin lug shank couplings and combination nipples. Refer to your individual coupling sheets for type and pricing.