

T253AA



150 PSI WATER DISCHARGE

APPLICATION

High pressure, 150 PSI lay flat type hose for general construction and mine water discharge.

COVER

Black weather and ozone-resistant EPDM rubber.

REINFORCEMENT

High tensile textile cords.

TUBE

Black EPDM rubber.

TEMPERATURE RANGE

-22°F to 176°F

STANDARD LENGTH

100 feet: 1 1/2" through 10"

50 feet: 6", 8" 10" & 12"

† WORKING PRESSURE

150 PSI constant (10 Bar) EXCEPT 12" (100 PSI)

BRANDING

ALFAGOMMA – ITALY – T253 10 BAR (150 PSI) GENERAL PURPOSE EPDM (in green letters) – 1" through 10": Solid Green Stripe on 12" ID

* 6 5/8" referred to as Elephant Trunk Hose — Ideal for "Irrigation Boots"

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MAX. REC. WP (PSI)
	(in.)	(mm)	(in.)	(mm)		
T253AA150	1 1/2	38	1.81	46	36	150
T253AA200	2	51	2.32	59	50	150
T253AA250	2 1/2	63	2.80	71	60	150
T253AA300	3	76	3.31	84	86	150
T253AA400	4	102	4.33	110	120	150
T253AA600	6	152	6.38	162	199	150
* T253AA662	6 5/8	168	7.01	178	216	150
T253AA800	8	203	8.46	215	298	150
T253AA1000	10	254	10.63	270	510	150
† T253AA1200	12	305	12.56	319	580	† 100

† Please note: 12" ID Maximum Working Pressure is 100 PSI and it is available only in 50' lengths.

COUPLING SUGGESTIONS

Cam and groove, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of quick-couplings, pin lug shank couplings and combination nipples. Refer to your individual coupling sheets for type and pricing.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE.