

## T350LL

WHITE COVER



## T351LL

WHITE COVER

## T351LG

GREEN COVER



### PREMIUM WHITE COVER PAPER MILL CREAMERY WASH DOWN HOSE — NO NOZZLE

#### APPLICATION

For general wash down service, using hot water or low pressure saturated steam in processing plants.

#### COVER

White, heat and abrasion-resistant EPDM rubber.

#### REINFORCEMENT

High tensile textile cords.

#### TUBE

White EPDM rubber.

#### TEMPERATURE RANGE

-40°F to 330°F

#### STANDARD LENGTH

200 feet — Eliminates bulky hookups.

#### WORKING PRESSURE

Constant Pressure — 15 Bar (225 PSI)

#### STEAM PRESSURE

Constant Pressure — 7 Bar (100 PSI)

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.
	(in.)	(mm)	(in.)	(mm)	
T350LL050	1/2	13	0.91	23	26
T350LL075	3/4	19	1.22	31	43
T350LL100	1	25	1.46	37	54

#### COUPLING SUGGESTIONS

Short shank, long shank couplings (NPT, GHT), barbed inserts attached with bands.

### PREMIUM PAPER MILL CREAMERY WASH DOWN HOSE WITH TAPERED NOZZLE

#### APPLICATION

For general wash down service, using hot water or low pressure saturated steam in processing plants.

#### COVER

White or green, heat and abrasion-resistant EPDM rubber.

#### REINFORCEMENT

High tensile textile cords.

#### TUBE

White EPDM rubber.

#### TEMPERATURE RANGE

-40°F to 248°F

#### STANDARD LENGTH

50 feet including 6" long built-in tapered nozzle.

#### WORKING PRESSURE

Constant Pressure — 10 Bar (150 PSI)

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.
	(in.)	(mm)	(in.)	(mm)	
T351LL/LG075	3/4	19	1.22	31	43
T351LL/LG100	1	25	1.46	37	52
T351LL/LG125	1 1/4	32	1.81	46	77
T351LL/LG150	1 1/2	38	2.05	52	91

#### COUPLING SUGGESTIONS

Short shank, long shank couplings (NPT, GHT), barbed inserts attached with bands.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE.