

# T404LL

# T403LB

**Increased OD on 1", 1½" & 2" Sizes**



## ‡ WHITE FOOD TRANSFER HOSE

### APPLICATION

The suction or discharge of edible oil-based food products.

**Hose may be sterilized with 30 PSI steam at 266° F for 30 minutes *maximum* – open end only.**

★ Not recommended for dry abrasive materials.

### COVER

Non-marking white, SBR/EPDM blended rubber.

### REINFORCEMENT

Spiralled high tensile textile cords, and 4 highly flexible steel helix wires.

### TUBE

White nontoxic chlorobutyl rubber, smooth. Meets FDA and 3A requirements.

### TEMPERATURE RANGE

-22°F to 176°F

### STANDARD LENGTH

100 feet

### WORKING PRESSURE

Constant Pressure — 10 Bar (150 PSI)

### BRANDING

ALFAGOMMA – ITALY T404 10 BAR (150 PSI) – GENERAL PURPOSE FOOD QUALITY – S & D (black letters)

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MIN. BEND RADIUS (in.)
	(in.)	(mm)	(in.)	(mm)		
T404LL100	1	25	1.46	37	62	3
T404LL150	1½	38	1.97	50	85	4
T404LL200	2	51	2.48	63	110	6
T404LL300	3	76	3.46	88	174	9
T404LL400	4	102	4.57	116	240	12

### COUPLING SUGGESTIONS

Cam and groove or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of quick-couplings and combination nipples. Refer to your individual coupling sheets for type and pricing.

‡ T404LE (Blue Cover) available as a special order item.

## GREY FOOD TRANSFER HOSE

### APPLICATION

The suction or discharge of edible oil-based food products.

**Hose may be sterilized with 30 PSI steam at 266° F for 30 minutes *maximum* – open end only.**

★ Not recommended for dry abrasive materials.

### COVER

Non-marking grey, SBR/EPDM blended rubber.

### REINFORCEMENT

Spiralled high tensile textile cords, and 4 highly flexible steel helix wires.

### TUBE

White nontoxic chlorobutyl rubber, smooth. Meets FDA and 3A requirements.

### TEMPERATURE RANGE

-22°F to 176°F

### STANDARD LENGTH

100 feet

### WORKING PRESSURE

Constant Pressure — 10 Bar (150 PSI)

### BRANDING

ALFAGOMMA – ITALY T403 10 BAR (150 PSI) – FOOD TRANSFER – S & D (in black letters)

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MIN. BEND RADIUS (in.)
	(in.)	(mm)	(in.)	(mm)		
T403LB200	2	51	2.56	65	126	8
T403LB300	3	76	3.54	90	200	12

### COUPLING SUGGESTIONS

Cam and groove or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of quick-couplings and combination nipples. Refer to your individual coupling sheets for type and pricing.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE.