

T600AA



HARD WALL MARINE EXHAUST HOSE

APPLICATION

Fuel, oil and hydraulic fluids suction and delivery with up to 50% aromatic content. Suitable for exhaust gas from water cooled stationary or marine diesel engines.

COVER

Black NBR/PVC blend — abrasion, ozone, hydrocarbon and fire resistant.

REINFORCEMENT

High tensile textile cords and **4** highly flexible steel helix wires.

TUBE

Black NBR — exhaust gas, fuel and fire resistant.

TEMPERATURE RANGE

-22°F to 212°F

STANDARD LENGTH

25, 50 or 100 feet

BRANDING

ALFAGOMMA – ITALY T600 MARINE EXHAUST/FUEL S & D – <SIZE> – USCG/SAE J1527 TYPE B2 (in red letters)

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MAX. REC. WP (PSI)	MIN. BEND RADIUS (in.)
	(in.)	(mm)	(in.)	(mm)			
T600AA062	5/8	16	1.02	26	38	75	2
T600AA075	3/4	19	1.18	30	46	75	2 1/2
T600AA087	7/8	22	1.26	32	51	75	3
T600AA100	1	25	1.38	35	57	75	3
T600AA112	1 1/8	28	1.50	38	61	75	3 1/2
T600AA125	1 1/4	32	1.65	42	67	75	3 1/2
T600AA137	1 3/8	35	1.77	45	73	75	4
T600AA150	1 1/2	38	1.89	48	78	75	4 1/2
T600AA162	1 5/8	42	2.05	52	84	75	5
T600AA175	1 3/4	45	2.16	55	90	75	5 1/2
T600AA189	1 7/8	48	2.28	58	95	75	5 1/2
T600AA200	2	51	2.40	61	100	75	6
T600AA225	2 1/4	57	2.64	67	110	75	6 1/2
T600AA238	2 3/8	60	2.76	70	128	75	7
T600AA250	2 1/2	63	2.87	73	134	75	7 1/2
T600AA275	2 3/4	70	3.11	80	146	75	8
T600AA300	3	76	3.39	86	160	75	9
T600AA350	3 1/2	90	3.94	100	189	75	10 1/2
T600AA400	4	102	4.41	112	212	75	12
T600AA450	4 1/2	115	5.08	129	276	75	13 1/2
T600AA500	5	127	5.55	141	337	75	14

T653AA



NEW PRODUCT

SOFT WALL MARINE EXHAUST HOSE

APPLICATION

Fuel, oil, bilge and water discharge applications.

COVER

Black NBR/PVC blend — abrasion, ozone, hydrocarbon and fire resistant.

REINFORCEMENT

High tensile textile cords.

TUBE

Black NBR

TEMPERATURE RANGE

-22°F to 212°F

STANDARD LENGTH

12 1/2 feet in straight lengths

BRANDING

ALFAGOMMA – ITALY – T653 SOFTWALL MARINE WET EXHAUST SAE J2006 R1 <SIZE> <YYYY MFG> (in blue letters)

Available Fall 2003

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MAX. REC. WP (PSI)
	(in.)	(mm)	(in.)	(mm)		
T653AA100	1	25	1.38	35	46	75
T653AA112	1 1/8	28	1.50	38	50	75
T653AA125	1 1/4	32	1.65	42	56	75
T653AA137	1 3/8	35	1.77	45	60	75
T653AA150	1 1/2	38	1.89	48	65	75
T653AA162	1 5/8	42	2.05	52	71	75
T653AA175	1 3/4	45	2.16	55	76	75
T653AA189	1 7/8	48	2.28	58	80	75
T653AA200	2	51	2.48	63	104	75
T653AA225	2 1/4	57	2.72	69	114	75
T653AA238	2 3/8	60	2.91	74	143	75
T653AA250	2 1/2	63	3.03	77	149	75
T653AA300	3	76	3.54	90	178	75
T653AA350	3 1/2	90	4.09	104	180	75
T653AA400	4	102	4.57	116	201	75
T653AA450	4 1/2	115	5.08	129	225	75
T653AA500	5	127	5.55	141	248	75
T653AA600	6	152	6.54	166	292	75
T653AA662	6 5/8	168	7.24	184	387	75
T653AA800	8	203	8.70	221	533	75

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE.