

T605AA



T605AH



BLACK PETROLEUM SUCTION HOSE

APPLICATION

For suction and discharge applications in truck and tank car transfer of gasoline, oil and other petroleum-based products with up to 50% aromatic content.

COVER

Black Nitrile PVC. Abrasion and ozone resistant.

REINFORCEMENT

High tensile textile cords and 4 highly flexible steel helix wires.

TUBE

Black conductive NBR.

TEMPERATURE RANGE

-40°F to 212°F

STANDARD LENGTH

100 feet: 3/4" through 6"
20 feet: 6"

WORKING PRESSURE

Constant Pressure 150 PSI

BRANDING

ALFAGOMMA – ITALY T605 – 10 BAR (150 PSI)
PETROLEUM – S & D (in red letters)

★ T605 is not recommended for use on a reel.

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MIN. BEND RADIUS (in.)
	(in.)	(mm)	(in.)	(mm)		
T605AA075	3/4	19	1.14	29	41	4
T605AA100	1	25	1.38	35	52	5
T605AA125	1 1/4	32	1.65	42	62	6
T605AA150	1 1/2	38	1.89	48	71	7
T605AA200	2	51	2.44	62	94	10
T605AA250	2 1/2	63	2.95	75	143	12
T605AA300	3	76	3.46	88	171	15
T605AA400	4	102	4.57	116	230	20
T605AA600	6	152	6.69	170	480	30

COUPLING SUGGESTIONS

Cam and groove, combination nipples attached with bands or internally expanded brass couplings with gasket seal attached with ferrules.

★ Kuriyama offers a full line of quick-couplings and combination nipples. Refer to your individual coupling sheets for type and pricing.

RED PETROLEUM SUCTION HOSE

APPLICATION

For suction and discharge applications in truck and tank car transfer of gasoline, oil and other petroleum-based products with up to 50% aromatic content.

COVER

Red Nitrile PVC. Abrasion and ozone resistant.

REINFORCEMENT

High tensile textile cords and 4 highly flexible steel helix wires.

TUBE

Black conductive NBR.

TEMPERATURE RANGE

-40°F to 212°F

STANDARD LENGTH

100 feet

WORKING PRESSURE

Constant Pressure 150 PSI

BRANDING

ALFAGOMMA – ITALY T605 – 10 BAR (150 PSI)
PETROLEUM – S & D (in yellow letters)

★ T605 is not recommended for use on a reel.

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MIN. BEND RADIUS (in.)
	(in.)	(mm)	(in.)	(mm)		
T605AH150	1 1/2	38	1.89	48	71	7
T605AH200	2	51	2.40	61	94	10
T605AH300	3	76	3.46	88	171	15
T605AH400	4	102	4.57	116	230	20

COUPLING SUGGESTIONS

Cam and groove, combination nipples attached with bands or internally expanded brass couplings with gasket seal attached with ferrules.

★ Kuriyama offers a full line of quick-couplings and combination nipples. Refer to your individual coupling sheets for type and pricing.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE.