

T720LG

T760LB



MATERIAL HANDLING HOSE — FDA GRADE

APPLICATION

Suction or discharge of wet or dry abrasive materials. Suitable for handling materials for human consumption.

COVER

Green SBR/EPDM blend — abrasion and ozone resistant.

REINFORCEMENT

Spiralled high tensile textile cords, with **4** highly flexible steel helix wires and static wire.

TUBE

3/16" thick white natural rubber. Meets FDA requirements.

TEMPERATURE RANGE

-22°F to 176°F

STANDARD LENGTH

100 feet: 2" through 4"

20 feet: 5", 6" and 8"

50 feet: 4" and 6"

WORKING PRESSURE

See chart below.

BRANDING

ALFAGOMMA – ITALY T720 – BULK FOOD & MATERIAL – S & D (in white letters)

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MAX. REC. WP (PSI)	MIN. BEND RADIUS (in.)
	(in.)	(mm)	(in.)	(mm)			
T720LG200	2	51	2.64	67	122	150	6
T720LG300	3	76	3.62	92	191	150	9
T720LG400	4	102	4.65	118	254	150	12
T720LG500	5	127	5.71	145	373	75	20
T720LG600	6	152	6.69	170	460	75	24
T720LG800	8	203	8.78	223	692	75	32

★ Please note: Proper grounding of static wire will prolong tube life.

COUPLING SUGGESTIONS

Cam and groove, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of quick-couplings, pin lug shank couplings and combination nipples. Refer to your individual coupling sheets for type and pricing.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE.

DRY BULK FOOD DISCHARGE — FDA GRADE

APPLICATION

Discharge or delivery of dry bulk food products.

COVER

Grey, abrasion-resistant SBR rubber.

REINFORCEMENT

Spiralled high tensile textile cords and static wire.

TUBE

3/16" thick white natural rubber. Meets FDA requirements.

TEMPERATURE RANGE

-22°F to 176°F

STANDARD LENGTH

100 feet.

BRANDING

ALFAGOMMA – ITALY T760 5 BAR (75 PSI) – HEAVY DUTY – BULK FOOD & MATERIAL DELIVERY (in white letters)

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MAX. REC. WP (PSI)
	(in.)	(mm)	(in.)	(mm)		
T760LB400	4	102	4.65	118	205	75

★ Please note: Proper grounding of static wire will prolong tube life.

COUPLING SUGGESTIONS

Cam and groove coupling attached with bands.

★ Kuriyama offers a full line of quick-couplings, pin lug shank couplings and combination nipples. Refer to your individual coupling sheets for type and pricing.