

T757AA



600 PSI PLASTER AND CONCRETE HOSE

APPLICATION

Designed for pumping plaster, grout, and wet cement to placement sites.

COVER

Black, conductive SBR/NR blend.

REINFORCEMENT

High tensile textile cords.

TUBE

Black conductive NR.

TEMPERATURE RANGE

-22°F to 176°F

STANDARD LENGTH

100 feet

WORKING PRESSURE

Constant Pressure — 40 Bar (600 PSI)

BRANDING

ALFAGOMMA – ITALY T757 – 40 BAR (600 PSI)
PLASTER & CONCRETE (in white letters)

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.
	(in.)	(mm)	(in.)	(mm)	
T757AA150	1½	38	2.13	54	82
T757AA200	2	51	2.64	67	111
T757AA300	3	76	4.09	104	297
* T757AA400	4	102	5.12	130	383

*Special Order Only

COUPLING SUGGESTIONS

Tubular steel full flow male permanently swaged or internally expanded with ferrule to provide maximum hose coupling compatibility.

T758AA

BLACK COVER

T758AE

BLUE COVER



800 PSI PLASTER, GROUT AND CONCRETE HOSE

APPLICATION

Designed for pumping plaster, grout, wet cement to construction placement sites at rated pressures.

COVER

BLACK — SBR/Natural Rubber
BLUE — SBR/EPDM

REINFORCEMENT

Spiralled high tensile textile cords.

TUBE

Black conductive NR — abrasion-resistant.

TEMPERATURE RANGE

-22°F to 176°F

STANDARD LENGTH

100 feet

WORKING PRESSURE

Constant Pressure — 55 Bar (800 PSI)

BRANDING

ALFAGOMMA – ITALY T758 – 55 BAR (800 PSI)
PLASTER & CONCRETE (in white letters)

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.
	(in.)	(mm)	(in.)	(mm)	
T758AA/AE100	1	25	1.57	40	58
T758AA/AE125	1¼	32	1.93	49	84
T758AA/AE150	1½	38	2.28	58	110
T758AA/AE200	2	51	2.80	71	145

COUPLING SUGGESTIONS

Tubular steel full flow male permanently swaged or internally expanded with ferrule to provide maximum hose coupling compatibility.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE.