

T760AA



LIGHT WEIGHT DRY POWDER DELIVERY HOSE

APPLICATION

Discharge of dry powders under low pressure, such as cement, grains and animal feed transfer.

COVER

Black conductive SBR/NR blend — abrasion and ozone resistant.

REINFORCEMENT

Spiralled high tensile textile cords.

TUBE

3/16" thick black static conducting natural rubber, compounded to resist cutting by abrasive materials.

TEMPERATURE RANGE

-22°F to 176°F

STANDARD LENGTH

100 feet

WORKING PRESSURE

Constant Pressure — 5 Bar (75 PSI)

BRANDING

ALFAGOMMA – ITALY T760 5 BAR (75 PSI)
BULK MATERIAL DELIVERY (in white letters)

★ Excessive bending during operation may cause premature wear.

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.
	(in.)	(mm)	(in.)	(mm)	
T760AA400	4	102	4.53	115	161

COUPLING SUGGESTIONS

Cam and groove, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of quick-couplings, pin lug shank couplings and combination nipples. Refer to your individual coupling sheets for type and pricing.

T763AA



HEAVY WEIGHT DRY POWDER DELIVERY HOSE

APPLICATION

Discharge of dry powders under low pressure. Pneumatic transfer of dry materials and abrasive slurries.

COVER

Black conductive SBR/NR blend — abrasion and ozone resistant.

REINFORCEMENT

Spiralled high tensile textile cords.

TUBE

1/4" thick black static conducting natural rubber, compounded to resist cutting by abrasive materials.

TEMPERATURE RANGE

-22°F to 176°F

STANDARD LENGTH

100 feet

WORKING PRESSURE

Constant Pressure — 5 Bar (75 PSI)

BRANDING

ALFAGOMMA – ITALY T763 5 BAR (75 PSI)
BULK MATERIAL DELIVERY (in green letters)

★ Excessive bending during operation may cause premature wear.

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.
	(in.)	(mm)	(in.)	(mm)	
T763AA400	4	102	4.72	120	215
T763AA500	5	127	5.71	145	264

COUPLING SUGGESTIONS

Cam and groove, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of quick-couplings, pin lug shank couplings and combination nipples. Refer to your individual coupling sheets for type and pricing.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE.