

T957LL



FURNACE DOOR COOLANT HOSE

APPLICATION

To convey cooling water to furnace doors in steel mills, glass plants, foundries, or where the hose is subjected to high temperatures and splashes of white-hot molten metals or glass.

COVER

Heat resistant tan EPDM, non-conductive resin-coated dust-free fiberglass cover.

REINFORCEMENT

High tensile textile cords.

TUBE

White non-conductive EPDM rubber.

TEMPERATURE RANGE

Tube: -40°F to 248°F

Cover: -40°F to 1000°F

STANDARD LENGTH

100 feet

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MAX. REC. WP (PSI)
	(in.)	(mm)	(in.)	(mm)		
T957LL075	3/4	19	1.30	33	47	150
T957LL100	1	25	1.54	39	58	150
T957LL125	1 1/4	32	1.89	48	84	150
T957LL150	1 1/2	38	2.13	54	98	150
T957LL200	2	51	2.64	67	126	150

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE.