



General Purpose Water Discharge Hose



Features & Benefits

- A tough, economical, general purpose PVC water discharge hose featuring polyester yarn reinforcement and homogeneous PVC cover and tube.
- For applications requiring low to medium working pressure.
- Ideally-suited for construction, agricultural, mining and general open end water discharge applications.
- Homogeneous virgin PVC construction eliminates separation of tube and cover.
- High tensile polyester yarn reinforcement provides strength and durability.
- All hose coils have PVC cores for easier dispensing.
- Hoses coil flat for easy storage.

Service Temperature: -5° F (-20° C) to 170° F (+76° C)

NUFLO™ General Purpose Water Discharge Hose

Series No.	Nominal Size (In.)	Hose ID (In.)	Approximate Wall Thickness (In.)	Working Pressure (PSI)	Coil Length (ft.)	Approx. Weight (lbs./coil)
BLUENF075	3/4	.827	.051	70	300	27.0
BLUENF100	1	1.063	.051	70	300	31.0
BLUENF125	1 1/4	1.378	.051	70	300	35.0
BLUENF150	1 1/2	1.614	.051	70	300	42.0
BLUENF200	2	2.106	.053	65	300	55.0
BLUENF250	2 1/2	2.598	.057	60	300	75.0
BLUENF300	3	3.090	.059	60	300	93.0
BLUENF400	4	4.094	.061	60	300	126.0
BLUENF500	5	5.079	.069	40	300	192.0
BLUENF600	6	6.142	.071	45	300	223.0
BLUENF800	8	8.150	.090	45	300	351.0

★ Kuriyama offers a full line of quick-couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama Couplings and Accessories Catalog for type and pricing.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE.