



NOTE: Service life may vary depending on operating conditions and type of material being conveyed.

Service Temperature Range

-40° F to 150° F

Actual service temperature range is application-dependent.

Series CF

“Cold Flex”
heavy duty
low-temperature
PVC general purpose
suction and transfer hose

Features and Benefits

- **Black HMW PVC convoluted construction** — provides great flexibility in sub-zero temperatures.
- **Smooth bore construction** — allows unrestricted material flow.
- All sizes full vacuum rated at 68°F.

General Applications

- Low temperature suction applications.
- Liquid manure handling.
- Septic tank cleaning.
- Dry fertilizer broadcasting.

Series	Nominal				Working Pressure (PSI)		Vacuum Rating (In. Hg)		Approx. Bending Radius @ 68°F	Standard Length (Ft)	Approx. Wt. (lbs/ft.)
	ID (In.)	ID (mm)	OD (In.)	OD (mm)	68°F	104°F	68°F	104°F			
CF150	1½	38.1	1.84	46.7	100	65	Full	28	3"	100	.40
CF200	2	50.8	2.41	61.2	100	65	Full	28	4"	100	.75
CF250	2½	63.5	2.93	74.5	90	55	Full	28	6"	100	.99
CF300	3	76.2	3.59	91.2	80	50	Full	28	7"	100	1.34
CF400	4	101.6	4.67	118.6	65	35	Full	28	11"	100	2.15
CF600	6	152.4	6.87	174.4	50	25	Full	28	18"	100/50/20	3.76



TigerClamp™
Spiral Double Bolt Clamps
available — see Page 29

Note: Service life may vary depending on operating conditions and type of material being conveyed.

Service Temperature Range

-40° F to 150° F

Actual service temperature range is application-dependent.

**Even Better!
New Improved
Compounds**

Series BW

“Blue Water”
Multi-purpose
low temperature
suction and transfer hose

Features & Benefits

- **HMW PVC clear construction** — allows for visual confirmation that material is flowing.
- **HMW PVC body** — provides sub-zero flexibility . . . increased abrasion-resistance compared to standard PVC.
- **Smooth cover** — makes clamping easy. Convoluted cover on 5" & 6" for greater flexibility.
- **Clear body with blue helix** — provides easy identification.

General Applications

- General water suction & transfer
- Construction, rental & mining
- Agricultural applications
- Irrigation lines
- Abrasive liquid applications

Series	Nominal				Working Pressure (PSI)		Vacuum Rating (In. Hg)		Approx. Bending Radius @ 68°F	Standard Length (Ft)	Approx. Wt. (lbs/ft.)
	ID (In.)	ID (mm)	OD (In.)	OD (mm)	68°F	104°F	68°F	104°F			
BW075	¾	19.1	1.01	25.6	115	75	Full	28	3"	100	0.19
BW100	1	25.4	1.26	32.0	90	65	Full	28	3"	100	0.22
BW125	1¼	31.8	1.56	39.6	90	65	Full	26	4"	100	0.36
BW150	1½	38.1	1.79	45.5	90	65	Full	26	5"	100	0.48
BW200	2	50.8	2.35	59.8	90	65	Full	26	7"	100	0.62
BW250	2½	63.5	2.87	73.0	70	48	Full	26	8"	100	0.87
BW300	3	76.2	3.43	87.0	65	45	Full	26	10"	100	1.23
BW400	4	101.6	4.49	114.0	55	40	Full	26	15"	100	1.83
BW500	5	127.0	5.57	141.5	45	30	28	24	25"	100/20	2.42
BW600	6	152.4	6.69	170.0	40	25	28	22	30"	100/20	3.36

KTFC0504

Because we continually examine ways to improve our products, we reserve the right to alter specifications without notice.

Abrasion Resistant
Liquid
Dry
Low Temp.
Abrasion Resistant
Liquid
Clear Hose
Dry
Low Temp.