



NOTE: Service life may vary depending on operating conditions and type of material being conveyed. Not for liquid handling use.

### Service Temperature Range

-4° F to 150° F

Actual service temperature range is application-dependent.

## Series GTF

PVC food grade lightweight blower and ducting hose

### Features and Benefits

- **Clear PVC construction** — complies with all applicable FDA† and USDA★ requirements and 3-A Sanitary Standards¶ . . . allows visual confirmation that material is flowing.
- **Exposed helix design** — provides high abrasion-resistance with increased flexibility . . . slides easily for ease of handling.
- **Smooth bore construction** — eliminates material build-up.

### General Applications

- In-plant blower and ducting applications requiring a food grade hose.
- Material chutes.
- Pharmaceutical product transfer.

Series	Nominal ID (In.)	Nominal ID (mm)	Nominal OD (In.)	Nominal OD (mm)	Working Pressure (PSI)		Vacuum Rating (In. Hg)		Approx. Bending Radius @ 68°F	Standard Length (Ft)	Approx. Wt. (lbs/ft.)
					68°F	104°F	68°F	104°F			
GTF150	1½	38.1	1.82	46.2	20	7	22	14	1"	50	.23
GTF200	2	50.8	2.39	60.8	15	6	21	12	2"	50	.30
GTF250	2½	63.5	2.89	73.4	10	5	19	10	2"	50	.39
GTF300	3	76.2	3.46	87.9	10	5	18	10	3"	50	.50
GTF400	4	101.6	4.50	114.3	8	4	13	7	3"	50	.77
GTF600	6	152.4	6.54	166.1	6	3	7	5	6"	50	1.08
GTF800	8	203.2	8.59	218.2	4	2	5	3	8"	50	1.74

† FDA — CFR Title 21 Parts 170 to 199.

★ USDA — For use in Federally-inspected meat and poultry plants.

¶ 3-A Sanitary Standard — No. 20-20, Multi-use plastic materials as product contact surfaces in equipment for production, processing and handling of milk and milk products.

NOTE: Available with embedded copper grounding wire upon request . . . Check with factory for minimum quantity requirement.



TigerClamp™ Spiral Double Bolt Clamps available — see Page 29

CG

CG-SL

Note: Service life may vary depending on operating conditions and type of material being conveyed.

### Service Temperature Range

-4° F to 150° F

Actual service temperature range is application-dependent.



- Series CG is not slit
- Series CG-SL is factory-slit

## Series CG "Cover Guard"

CG: Light duty PVC ducting hose

CG-SL: Factory-Slit MSHA-listed PVC Conduit

### Features & Benefits

- **PVC construction** — clear PVC flexible with white helix . . . allows for visual confirmation of contents.
- **MSHA (US Government) listed** — for flame-resistance for use in mines.
- **White exposed helix design** — provides increased flexibility and slides easily for ease of handling.
- **Smooth bore construction** — eliminates material build up.

### General Applications

- Mine supply line cover protection
- Dust collection • Fume removal
- Air vent lines • Cable protection

Series	Nominal ID (In.)	Nominal ID (mm)	Nominal OD (In.)	Nominal OD (mm)	Working Pressure (PSI)		Vacuum Rating (In. Hg)		Approx. Bending Radius @ 68°F	Standard Length (Ft)	Approx. Wt. (lbs/ft.)
					68°F	104°F	68°F	104°F			
CG-SL100	1	25.4	1.28	31.9	n/a	n/a	n/a	n/a	.5"	100	0.14
CG-SL125	1¼	31.8	1.51	38.4	n/a	n/a	n/a	n/a	.75"	100	0.18
CG-SL150	1½	38.1	1.76	45.1	n/a	n/a	n/a	n/a	1"	100	0.21
CG/CG-SL200	2	50.8	2.30	58.4	12	6	10	5	2"	100	0.28
CG238	2¾	60.3	2.76	70.1	12	6	10	5	2"	100	0.38
CG/CG-SL250	2½	63.5	2.81	71.3	10	5	8	4	2"	100	0.39
CG/CG-SL300	3	76.2	3.35	85.0	8	4	7	3	3"	100	0.45
CG/CG-SL350	3½	88.9	3.83	97.4	8	4	7	3	3"	100	0.51

KTFCA0903

Because we continually examine ways to improve our products, we reserve the right to alter specifications without notice.

