



TigerClamp™
Spiral Double Bolt Clamps
available — see Page 29

NOTE: Service life may vary depending on operating conditions and type of material being conveyed.

Service Temperature Range

-4° F to 150° F

Actual service temperature range is application-dependent.



Series	Nominal				Working Pressure (PSI)		Vacuum Rating (Inches Hg)		Approx. Bending Radius @ 68°F	Standard Length (Ft)	Approx. Wt. (lbs/ft.)
	ID (In.)	ID (mm)	OD (In.)	OD (mm)	68°F	104°F	68°F	104°F			
WSTF300	3	76.2	3.62	92.0	70	35	Full	28	6"	100/20	1.13
WSTF400	4	101.6	4.76	121.0	65	32	Full	28	8"	100/20	1.74
WSTF500	5	127.0	5.98	151.9	50	25	28	25	11"	100/20	2.95
WSTF600	6	152.4	7.17	182.1	50	25	28	25	13"	100/20	3.88

† FDA — CFR Title 21 Parts 170 to 199.

★ USDA — For use in Federally-inspected meat and poultry plants.

¶ 3-A Sanitary Standard — No. 20-20, Multi-use plastic materials as product contact surfaces in equipment for production, processing and handling of milk and milk products.

Series WSTF

Heavy duty PVC
food grade
suction/discharge hose

Features & Benefits

- **Clear flexible PVC construction with synthetic reinforcement** — ideal for both suction and discharge applications . . . complies with all applicable FDA† and USDA★ requirements and 3-A Sanitary Standards¶ . . . allows visual confirmation that material is flowing.
- **White exposed PVC helix design** — provides excellent strength characteristics while permitting hose to slide easily.
- **Smooth bore** — eliminates material build up.

General Applications

- Food processing, bottling, wine-making, dairy, brewing, canning.



TigerClamp™
Spiral Double Bolt Clamps
available — see Page 29

NOTE: Service life may vary depending on operating conditions and type of material being conveyed.

Service Temperature Range

-4° F to 150° F

Actual service temperature range is application-dependent.



Series	Nominal				Working Pressure (PSI)		Vacuum Rating (Inches Hg)		Approx. Bending Radius @ 68°F	Standard Length (Ft)	Approx. Wt. (lbs/ft.)
	ID (In.)	ID (mm)	OD (In.)	OD (mm)	68°F	104°F	68°F	104°F			
WST300	3	76.2	3.62	92.0	70	35	Full	28	6"	100/20	1.13
WST400	4	101.6	4.76	121.0	65	32	Full	28	8"	100/20	1.74
WST500	5	127.0	5.98	151.9	50	25	28	25	11"	100/20	2.95
WST600	6	152.4	7.17	182.1	50	25	28	25	13"	100/20	3.88

Series WST

Heavy duty PVC
suction/discharge hose

Features & Benefits

- **Clear flexible PVC construction with synthetic reinforcement** — ideal for both suction and discharge applications . . . allows visual confirmation that material is flowing.
- **Gray exposed PVC helix design** — provides excellent strength characteristics while permitting hose to slide easily.
- **Smooth bore** — eliminates material build up.

General Applications

- Heavy duty suction and discharge.
- Rental/construction pumping.
- Fish suction.

